



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय  
OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

आ.ब: २०८३/०८४

च.नं.

मिति: २०८३/०६/०५

विषय: दररेट उपलब्ध गराउने सम्बन्धी सूचना ।

उपरोक्त सम्बन्धमा आ.व. २०८३/०८४ मा यस झिमरुक गाउँपालिका अन्तर्गत रहेका स्वास्थ्य सस्थाहरूका लागि औजार उपकरण, प्रयोगशाला सामग्री र सर्जिकल सम्बन्धि सामग्रीहरू आवश्यक भएकोले उल्लेखित स्पेसिफिकेन बमोजिमको सामग्रीहरू आफुले दिन सकिने दररेटमा सात (७) दिन भित्र पेश गर्नुहुन सम्बन्धित आपूर्तिकर्ता, फर्म र सरोकारवालाहरूका लागि यो सूचना प्रकाशित गरिएको छ । दररेट तपसिलको मेल आई. डि. मा पठाउन सकिने छ ।

तपसिल

| S.N. | Name of Equipment                         | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Unit price<br>Per Unit |
|------|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 1.   | Table, Examination                        | An examination table with upholstered top in two pieces. Adjustable headrest on metal ratchet and mattress, Bed shall be made of a solid steel sheet and plate construction with anti-corrosive and antirust treated epoxy powder coating with upholstered top, Overall size of the table shall not be less than 1830 mm L x 600mm W x 825 mm H., mattress shall be foldable and shall be designed to bend with the positioning of the bed when the backrest of the bed is adjusted, one-year warranty, Having ISO, CE or USFDA approved product certificate. |                        |
| 2.   | Patient Trolley                           | A Patient trolley for transferring the patient from ward to ward, Size: Approx. 2030 L x 560 W x 820 H mm, should be mounted on 150 mm dia. swivel castors with two brakes, Fixed stretcher on plywood with padded foam covered with Rexene, Stretcher should consist of back rest, Back rest should be adjustable on ratchet, Provision of cylinder, MS Railing & IV rod, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                           |                        |
| 3.   | Trolley, Emergency (Emergency Crash Cart) | Emergency trolley or (Emergency Crash Cart) is a set of trays/drawers/shelves on wheels used in hospitals for transportation and dispensing of emergency medication/equipment at site of medical/surgical emergency for life support protocols potentially to save a patient's life, Emer-                                                                                                                                                                                                                                                                    |                        |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र स्वस्थता”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np

वेबसाइट: jhimrukmun.gov.np  
अमरराज सेजकवि  
प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते प्युथान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|    |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |
|----|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|    |                                      | gency trolley (Emergency Crash Cart) with removable coloured bins, storage units, fitted with oxygen cylinder holder and electric lamp holder and four swivels castors, Dimensions: approx. 950mm L x 500mm W x 1500mm H., Fitted with epoxy powder coated oxygen cylinder holder and electric lamp holder with clamp and cardiac massage board, capable of carrying ECG Monitor/defibrillator and a suction apparatus, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                       |  |
| 4. | <b>Body Mass Index (BMI) Machine</b> | Body mass index (BMI) is an essential value for determining an adult's state of nutrition. Height in relation to weight provides information about whether a person is overweight, of normal weight or underweight, Digital display Type Ultrasonic BMI Machine complete unit with accessories, Height measurement via Ultrasonic sensor, Sufficient platform size to stabilize the human body, Platform should be made up of durable hardened plastic or rubber or tempered glass or metal, Auto Calibration for finer accuracy, Weighing Capacity: 200kg or more, Height Range :50 to 200 cm or more, Display Type: Digital LCD/LED, automatically measure weight, height & body mass index accurately and display it, one-year warranty, having ISO, CE or USFDA certified product. |  |
| 5. | <b>Defibrillator-Biphasic</b>        | The machine should have facility for ECG monitoring, Bi-Phasic Defibrillation with facility to print ECG through in-built thermal printer, TFT display with screen size at least 7" or more, have both Synchronous and Asynchronous mode, biphasic technology based having energy selection of 2-300 Joules, capable of monitoring ECG through ECG cables, Multifunction electrodes and external paddles, able to defibrillate Adult, Paediatric patients, should be compact, portable with built in rechargeable battery, able to provide metronome signal for CPR, Must submit ISO13485 for Medical Devices AND certified with EU-CE or US-FDA (510K).                                                                                                                               |  |

अमरराज सेजुवाल

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|    |                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6. | <b>Bed Side Patient Monitor</b>                       | A bedside multi-function patient monitor to monitor physiological parameters of all patient categories, at bedside, NICU, ICU OT or during transportation applicable for Adult, Pediatric and neonatal application, Patient monitor 5 parameter with ECG, Resp., SpO2, NIBP and Temp., All accessories, consumables, wall mounts and etc, High resolution at least 12" high resolution colour LED touch screen and upto 7 waveforms display, Protection against defibrillator discharge, facility of calculation of drug concentration, Should show Perfusion Index (PI) numeric, should support pace detection, Real Time ST complex view and comparison, ST analysis and ST templates, Real Time QT/QTc monitoring, 24 hours ECG analysis summery, Should be no fan design, one-year warranty, ISO, CE and USFDA(510k) approved product certificate. |
| 7. | <b>ECG Machine Portable (12 Channel) with Trolley</b> | Portable digital ECG machine, Trolley with complete accessories, must be able to acquire all 12 leads simultaneously, Min. 7" touch screen LCD display with display shows ECG-curves, heart rate, patient name and ID, time, speed and filter setting, Continuous check on the quality of electrodes connection, visual alert on loss of signal, Splash-resistant function keys, Appropriately protected for operation during defibrillation, Front panel provides indication of system and battery status, electrode connection, Built-in high-resolution thermal printer automatic and manual print-out mode, Rechargeable battery integrated in device, one year warranty, ISO, CE and USFDA approved product certificate.                                                                                                                          |
| 8. | <b>Electric Suction Machine</b>                       | The system consists of Suction machine with 2 glass/polycarbonate Jars, Mains Operated, Suction tubing, Oil immersed rotary vane pump, Flow Rate: 25-30 L/min, 2 glass/polycarbonate jars of capacity 1500 ml., Maximum Vacuum: -710 mmHg $\pm$ 10 mmHg, On/Off Switch and power indicator must be available, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 9. | <b>Oxygen Concentra-</b>                              | The Oxygen Concentrator should be small & portable, light in weight, Flow rate range 0.5~ 5 L/ min, Outlet pressure 20 KPA ~ 50 KPA, Alarm for Low High/Low Pressure Protec-                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य सुरक्षित आधार र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np

वेवसाइट : jhimrukmun.gov.np  
अमरराज सेजुवाल  
मुख्य प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय  
OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
|-----|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     | tor                                                                               | tion, Power Failure, Low Flow Rate, should have Sound level < 55 dB, should have working indicator, should have function of timing shut down, one-year warranty, Having ISO 13485, CE or USFDA approved product certificate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |  |
| 10. | Oxygen Cylinder, 46L                                                              | Oxygen cylinder for medical use, Cylinder filled with medical grade Oxygen, Seamless steel Oxygen cylinder with "Bull nose"-valve, Water Capacity: 46L, Working pressure: 15MPa(150bar), Testing Pressure: 250bar, All fitting of cylinder must be leak proof and shall not have any chances of leakages, supplied complete with cylinder key/spanner/bar or hand-wheel to turn cylinder on/off, certified to meet ISO9001 and ISO 9809 for seamless steel gas cylinders, Explosive Safety Test Certificates from IOL (Indian Oxygen Ltd.)/ Department of Explosion Government of India/ BOC (British Oxygen Company) or other national/international reputed institutions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |
| 11. | Oxygen Cylinder, 10L (with Trolley, Regulator & Flow Meter and Bubble Humidifier) | Oxygen Cylinder, 10L with Trolley, Regulator, Flow Meter and Bubble Humidifier, Cylinder filled with medical grade Oxygen, Seamless steel Oxygen cylinder with "Bull nose"-valve, Water Capacity: 10L, Working pressure: 15MPa(150bar), Testing Pressure: 250bar, All fitting of cylinder must be leak proof and shall not have any chances of leakages, Shall be supplied complete with cylinder key/spanner/bar or hand-wheel to turn cylinder on/off., Trolley: The trolley must have MS tubular frame work and SS base, Two large, minimum 100mm good quality wheels with rubber or similar rims, To hold F and E size (one filled cylinder at once) of medical oxygen cylinder. Regulator: Bull nose screw type, medical oxygen cylinder fitting, regulated to convert standard cylinder pressure (typically 2,000 psi) to approximately 4 BAR (4 atmospheres) pressure, Regulator must be diaphragm type needle valve regulators are NOT permitted. Flow Meter: Sturdy and reliable Flow Meter Unit for an accurate measuring of flow of gases, Flow rate range 0 – 15 litres / minute, Inlet pressure suitable for the cylinder, Bubble Humidifier with Safety Valve and Pressure Relief Valve: Humidifier jar must be steam autoclavable / gas sterilizable, Jar made of Unbreakable Poly |  |



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भयागुटे प्युठान  
BHYAGUTE PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |  |
|-----|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                        | Carbonate, certified to meet ISO9001 and ISO 9809 for seamless steel gas cylinders, Explosive Safety Test Certificates from IOL (Indian Oxygen Ltd.)/ Department of Explosion Government of India/ BOC (British Oxygen Company) or other national/international reputed institutions.                                                                                                                                                                                                                                                                                                                                                                       |  |
| 12. | Wheel Chair (foldable) | Basic foldable wheelchair for adult use, Heavy carriage mounted on 4 ball-bearing wheels, Front wheels free rolling, 360 degrees swivel, both rear wheels with brake, Foot lever, integrated in frame, facilitates tilting the wheelchair, Arm-rests seat and back are upholstered, <b>Materials:</b> High resistance to corrosion (tropical environment), Frame: Chrome-plated tubular steel, Tires: Heavy duty solid rubber, <b>Dimensions, Approx. <math>\pm 10\%</math>:</b> Overall: 450 x 500 x 870mm (d x w x h), Carrying capacity: Approximately 100kg, One-year warranty, having ISO 9001 or ISO 13485, CE or USFDA approved product certificate. |  |
| 13. | Patient Trolley        | A Patient trolley for transferring the patient from ward to ward, Size: Approx. 2030 L x 560 W x 820 H mm, should be mounted on 150 mm dia. swivel castors with two brakes, Fixed stretcher on plywood with padded foam covered with Rexene, Stretcher should consist of back rest, Back rest should be adjustable on ratchet, Provision of cylinder, MS Railing & IV rod, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                         |  |
| 14. | Stretcher              | Foldable stretcher for carrying patients who require medical care, Foldable stretcher with two light weight poles with handgrips, Open size: approximately 200cm L x 55cm W x 15cm H., Folded size: approximately 200cm L x 8cm W x 15cm H.<br><br>Poles: Two lightweight carrying poles made of non-ferrous metal like heavy duty Aluminium Alloy. These to be hollow tube poles with proper non-slip shaped handgrips, Stretcher material: Preferably in nylon or similar synthetic material but heavy duty canvas is acceptable, The material shall be turnover edged and then double stitched in nylon thread on                                        |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य”

ईमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट : jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL



|     |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |
|-----|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                              | all edges, one-year warranty, Having ISO/CE certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |
| 15. | Hospital Bed with mattress   | Hospital Bed epoxy powder coated with high density PU foam mattress, shall be anti-corrosive and antirust treated epoxy powder coated welded steel bar or epoxy powder coated 16gauge perforated sheet top to improve ventilation, patient bed shall be fixed height with 2 sections where the backrest section could be elevated by mechanical hand crank located at the foot-end of the bed, Bedhead and foot-end panel (head and foot bows) shall be made of either between 4-6 anti-corrosive and antirust treated epoxy powder coated vertical tubular tube of not less than 30mm in diameter, Both bedhead and foot-end panel shall be detachable, Shall provide with one no. Two section mattress of dimensions at least (2000mm L x 900mm W) with washable cover of good quality. The mattress must be made of high-density PU foam of 100mm thickness, having ISO ISO13485, CE or USFDA approved product certificate.                                |  |
| 16. | ICU Bed (Manually Operating) | ICU Bed (Manually Operating) with complete accessories, ICU Bed mainframe perforated heavy gauge sheet, base of the bed must have four sections, have X-Ray translucent back section made up of high pressure laminate, X-Ray cassette holder underneath the back section, Base frame & support frame must be made up of Stainless steel or pre-treated rust free oven baked epoxy powder coated washable paint, manual adjustment Height: 460-700mm, equipped with large castors (diameter 100mm approx.) with central braking/individual braking system and steering facility, Four section mattress, made up of high density foam with Anti-Microbial agent incorporated into all components that assists in prohibiting growth of bacteria & fungi and easy to clean, Dimensions of bed: Length: 2150 -2250mm, Width: 850 -1020mm, Mattress Size: appropriate as per bed size, , one-year warranty, Having ISO, CE or USFDA approved product certificate. |  |

*(Signature)*  
अमररज सेजवाल

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित वातावरणको विकास”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL



|     |                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 17. | Electric ICU Bed                               | ICU Bed mainframe perforated heavy gauge sheet. The system must be mobile and electrically operated adjustable for heights, trendelenburg etc., Ergonomic electric ICU bed shall be 4 motor controlled 5 function electric ICU Bed with complete accessories, base of the bed must have four sections, Base frame & support frame must be made up of Stainless steel or pre-treated rust free oven baked epoxy powder coated washable paint, have electrically adjustment of Height: 460-700mm, equipped with four articulated half-length tuck away side rails, equipped with large castors (diameter 100mm approx.) with central braking/individual braking system and steering facility, Four section mattress, made up of high density foam with Anti-Microbial agent incorporated into all components that assists in prohibiting growth of bacteria & fungi and easy to clean, Dimensions of bed: Length: 2150 -2250mm, Width: 850 -1020mm Mattress Size: appropriate as per bed size, , one-year warranty, Having ISO, CE or USFDA approved product certificate. |
| 18. | Bed Side Locker                                | Bed Side Locker for Keeping medicines, other items of patient in wards, ICU etc, Locker should be machine pressed from CRCA sheet with three sides closed, should have mild steel one box and a drawer, should be mounted on two 50 mm dia. Swivel castors & two legs on PVC stumps, should have stainless steel top, one-year warranty, having ISO 13485 for Medical Devices & CE certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| 19. | Mayo Trolley(Cardiac Trolley or Overbed table) | Mayo trolley with four swivels castors use in operating theatre and in treatment rooms, used for layout for surgical instruments, trolley shall be constructed fully with 304 grade stainless steel or better, Come with a removable 304 grade stainless steel tray size approximately 560mm x 400mm x 20mm, height adjustable, mobile on 4 x 50mm robust fully 360° swivel castors with non-marking grey tyres and at least 2 diagonal castors shall have brakes, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 20. | Patient Screen                                 | Epoxy powder coated three-fold patient screen, Patient Screen with light blue curtain and fully swivel twin wheel castors, Three-fold ward screen approx. total size 2450 w x 1650 mm, three section 600mm span width., and each foot to have two swivel castors size 50mm, Curtain must have no                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL



|     |                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  |
|-----|------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                                      | gaps between sections, having ISO 9001 or ISO 13485 or better for medical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |
| 21. | <b>Bed Gynaecological Examination &amp; Delivery</b> | Standard table for gynaecological examination and delivery for use in healthcare facilities, Fully stainless steel (S.S) Gynaecological examination and delivery table, 3 sections, Mounted on 4 sturdy supports, finished with rubber feet, All sections fitted with a padded mattress, Robust mechanics allow for manual repositioning between gynaecological and obstetric use, Fully Stainless Steel, Mattress: high-density polyurethane foam with density approx. 50mm or more, Mattress Cover: vinyl or vinylized nylon cover flexible, highly tear resistant, anti-static, flame retardant, disinfectant- and liquid proof, washable, Bowl or tray: Austenitic stainless steel 18/10, Approximate Dimensions: 1850L x 700W mm., Bed shall have a load capacity of at least 150kg, supply with Pair of telescopic drop down stainless steel side-rails, SS telescopic IV-pole with at least 2 hooks- 01 no., Pair of adjustable leg crutches with anti-static pads and fixation straps, SS liquid collection pan- 01 no. Must submit ISO 9001 or ISO13485, CE or USFDA approved product certificate |  |
| 22. | <b>Radiant Baby Warmer</b>                           | Radiant warmer is used to provide thermal support for babies, Microprocessor based servo controlled electronic controller, Should have SKIN, AIR and Manual Control modes or equivalents mode, Display should have Two bright LED digital displays combination of Red and Green to continues monitor of baby temp and set temp, with easily switchable to 0°C to 0°F, Main Unit should be Made with high quality mild steel fabrication, Base mounted on imported anti-skid casters with locking facility, Baby Tray four sides clear acrylic panels front and both Sides collapsible with both head up & down tilting facility, Clear acrylic base for under surface phototherapy unit with X-Ray cassette compartment, ceramic heater with parabolic reflector to maintain uniform temp across the baby bed Examination Latest power saving high bright LED, Side monitor tray provision to keep Monitor or Pulse Oximeter, having ISO ISO13485, CE or USFDA approved product certificate.                                                                                                               |  |
| 23. | <b>Resuscitation Set, Emergency</b>                  | Emergency resuscitation set is use in the hospitals for all emergency situations where respiratory support is needed, Silicon bellows - 250ml, 500ml & 1600ml one each, Non-rebreathing valve for adult, Non-rebreathing valve with                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित अवस्था र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np

प्रमुख अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |
|-----|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                                                   | 40cmH <sub>2</sub> O pressure release, 3600 swivelling patient connector, 1.5m PVC oxygen tubing, carrying pouch, one-year warranty, Having ISO/CE certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| 24. | <b>Phototherapy</b>                                               | Phototherapy machine is used for treatment for jaundice where the exposure of skin to a light source converts unconjugated bilirubin molecules into water soluble isomers that can be excreted by the usual pathways, LED lights should be controlled through micro controller, Irradiance : >45 $\mu\text{W}/\text{cm}^2/\text{nm}$ at a distance of 30 cm, have optical design to minimizes spill light outside the bed area, Wavelength should be from 450 to 465 nm narrow band, Should have Low & High setting Irradiance Adjustment, Lamp Usages Hours : >20,000 hrs, have Safety Temperature Cut-off function, having ISO ISO13485, CE or USFDA approved product certificate.                                    |  |
| 25. | <b>Binocular Microscope (LED)</b>                                 | Binocular Microscope (LED) with all the necessary adapters and power cords, Achromatic objectives 4x/0.10, 10x/0.25, 40x/0.65, 100x/ 1.65 (oil), LED illumination more than 20,000 hrs of operation, infinite Optical System , Quadruple Nosepiece, Binocular head.<br><br>Stage height movement, Coarse adjustment limit stopper, Torque adjustment for coarse adjustment knob,<br><br>Fine focus knob, Inclination: 30 degree<br><br>Rotation: 360 degree, Eye pieces must be WF 10x FN:20(aniti-fungus), warranty 2 years, having ISO, CE and USFDA listing product.                                                                                                                                                 |  |
| 26. | <b>Fully Automatic Hematology Analyzer (5-Parts Differential)</b> | Automated blood cell counter is used to count various types of blood cells in the blood that include reportable IG, There should be at least 30 reportable parameters including reportable Immature granulocytes, Measurement Principle DC sheath flow detection (RBC, PLT, HCT), cyanide free (HGB), wbc etc, Throughput: Atleast 60 samples per hour for CBC and Differential, should use cyanide free hemolyzing reagent, sampling probe must be automatically cleaned off, so that any blood stack doesn't occur, Automatic start-up, self-checks, rinsing and cleaning, should be supplied with all Reagents & consumables, calibrators & controls required to do at least 200 tests to be supplied during instal- |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np

वेबसाइट: jhimrukmun.gov.np

प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय  
OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |
|-----|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                              | lation, should supply Suitable UPS for minimum 30 min. backup for the entire system, one-year warranty, having ISO, EU_CE Marked compliance with in-Vitro Diagnostic Medical Device OR USFDA Certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |
| 27. | <b>Fully Automatic Biochemistry Analyzer</b> | A Fully Automated Biochemistry Analyzer is a medical laboratory instrument designed to perform a wide range of biochemical tests on blood, serum, plasma, urine, and other biological samples with minimal human intervention, Bench-top design and must be capable of doing at least 100 tests/hr, Light source shall be Halogen tungsten lamp or better, Reagent position must be at least 40 positions, In Built Reagent Cooling System, Reagent Probe cleaning shall be automatic with internal and external washing, Sample loading capacity of at least 40 samples at a time with continuous loading facility, have separate sample mixer, have internal sample barcode reader system, Auto-dilution and pre-dilution for sample, Reaction disk must have at least 50 cuvette position, reaction cuvette must be lifelong and must be permanent hard glass type, Water consumption used should not be more than 5L/H, Calibration mode: Real Time, Individual and cumulative quality control. Automatic QC programming required, one-year warranty, having ISO, CE Marked compliance with in-Vitro Diagnostic Medical Device OR USFDA Certified product. |  |
| 28. | <b>Centrifuge – Desktop 8 tubes 10-15 ml</b> | Centrifuges are required in the Laboratory to separate various components of Blood and any other liquid sample for analysis, Centrifuge – Desktop 8 tubes 10-15 ml, Microprocessor controlled, swing out rotor with buckets, Facilities, adaptors and accessories for 8 tubes of 10-15 ml, Should have Speed 1000-5000 RPM, Quiet operation and low vibration, Power switch ON/OFF, and timer control knob, having ISO, CE or USFDA certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |
| 29. | <b>Semi-Automated Bio-chemistry Analyser</b> | The Semi-Auto Chemistry Analyzer is required for routine biochemical testing in a clinical laboratory setting. The system should be reliable, user-friendly, and designed to deliver accurate and efficient test results with minimal maintenance, should have min. 4" touch screen display and min 250 test can be programmed, testing mode flow cell and cuvette, Built-in Incubator, Automatic by specially designed Peristaltic Pump, Light Source: 6V/10W Tungsten Halogen Lamp or better, should have in- Built thermal printer, Two-year warranty, Having ISO and CE or USFDA approved                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र स्वास्थ्य”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np

वेबसाइट: jhimrukmun.gov.np  
अमरराज सेजुवाल  
प्रमुख प्रशासक अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |
|-----|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                             | product Certificate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |  |
| 30. | Incubator, 30 Litres        | <p>Microprocessor/Microcontroller based digital controlled system, Incubator, 30 Litres capacity with all standard accessories, Natural convection, with adjustable thermostat for temperature setting, Temperature adjustable from 20 °C – 70 °C with temperature stability 37 °C, shall have two ventilators, Stainless steel interior chamber with minimum 2 shelves.</p> <p>LED/LCD display of parameters with membrane keypad for setting of parameters, shall have audio-visual alarm facility, It shall have double door with interior glass and exterior stainless steel, warranty 1 years, having ISO, CE or USFDA listing product.</p> |  |
| 31. | Hot Air Oven                | This oven is designed for laboratory and industrial applications requiring precise and reliable dry heat for processes such as drying, sterilizing, and heat treatment. The apparatus features a robust double-walled construction and is engineered for long-term performance and user safety. Digital Display Proportional Temperature Controller, Fuzzy Auto-Tuned PID Programmable Controller with single set point, Digital Timer Clock (0 to 24 Hours) having ISO, CE and USFDA listed product.                                                                                                                                            |  |
| 32. | Dry Bath, Digital Incubator | Dry bath incubators are used in laboratories to heat samples, Dry bath incubators are used in laboratories to heat samples prior to a variety of applications and are used widely in molecular, microbiological, and biochemistry labs, With dry block incubators, tubes are placed inside of heat block which even distributes heat, Microprocessor controlled programmable, digital display for temperature etc, Material: Metal Body, Temperature Controller: Digital Type, Temperature Range: 37°C to 70°C, Heating Block min. 24 holes, warranty 1 years, having ISO, CE or USFDA listing product.                                          |  |
| 33. | Refrigerator for lab (200L) | Refrigeration system: CFC-free refrigerant cooling system, Capacity of storage: min. 200 litres, Microprocessor based temperature control, Monitor for temperature with alarm, visual and sound, for high/low temperature, Should have clear product visibility with dual glass door, Temperature Range: 2°C ~ 8°C, one-year warranty, Having ISO 9001 or ISO 13485 AND CE Marking Compliance Electrical Safety                                                                                                                                                                                                                                  |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य सुरक्षित आधारमा विकास”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट : jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |
|-----|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                     | approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| 34. | <b>Electrolyte Analyzer</b>         | Electrolyte analyzer Based on ISE OR BISO technology, analyzer with integrated printer and with complete accessories, Microprocessor controlled electrolyte analyzer which can measure Na <sup>+</sup> , K <sup>+</sup> , Cl <sup>-</sup> , Analyzing time-less than 60 seconds/test, sample throughput of minimum 50 samples/hour, Maintenance free electrodes, have data display on built in 5" LCD display screen, have automatic flagging of abnormal result, one-year warranty, having ISO, CE or USFDA certified product. |  |
| 35. | <b>Protein Analyzer</b>             | Protein Analyzer complete with printer is required, All in one cartridge for single test, Colour Touch screen display, Test Parameters: at least HbA1c, CRP, D-Dimer, mALB, IgG, IgM, IgA, C3, C4 etc. should be available, Sample type: Whole blood, serum, plasma, urine, Auto identification of test by barcode on reagent cartridge, one-year warranty, having ISO, CE or USFDA certified product.                                                                                                                          |  |
| 36. | <b>Fixed volume micropipette</b>    | Fully autoclavable, Ergonomic design provides excellent operating experience, Easy-to-read volume display, Easy calibration and maintenance<br>provides excellent operating experience, Large display window allows for easy volume identification, Easy calibration and maintenance, Corrosion-resistant piston and ejector, Volume adjustment Protection, Fixed Volume:<br>❖ 20 µl<br>❖ 50 µl<br>❖ 100 µl<br>❖ 1000 µl<br>one-year warranty, having ISO, CE or USFDA certified product.                                       |  |
| 37. | <b>Variable volume micropipette</b> | Fully autoclavable, Ergonomic design provides excellent operating experience, Easy-to-read volume display, Easy calibration and maintenance, provides excellent operating experience, Large display window allows for easy volume identification, Easy calibration and maintenance, Corrosion-resistant piston and ejector, Volume adjustment Protection, Adjustable Volume:<br>❖ 5-50 µl<br>❖ 10-100 µl<br>❖ 100-1000µl                                                                                                        |  |



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL



|     |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |  |
|-----|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                              | one-year warranty, having ISO, CE or USFDA certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |
| 38. | <b>Trolley, Medicine</b>     | A medicine/drug trolley for storage and delivery of medicines and drugs to patients in wards of healthcare facilities, shall be constructed fully with 304 grade stainless steel sheet and tube or better, Overall size: approximately 900 H x 460 W x 760 L mm., Flat top of SS and at least 6 inch deep removable bucket at bottom, Multiple drawers (minimum 6) made of high quality materials with telescopic channels, below the platform, Minimum 6 small boxes to keep drugs, provision for hanging one IV fluid bottle, Shall be mobile on 4 x 50mm diameter (approx.) robust 360 deg., one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                           |  |
| 39. | <b>Dental Chair (Medium)</b> | Dental Chair-Medium complete unit and with all standard accessories, Electrical, operated water control for basin/bowl which is Ceramic, Body of the chair and unit is painted and rust proof, Sensor Controlled Lights with Halogen or LED light, High power motorized saliva ejector (2 bottles) with pressure gauge, Control box with water control – Air motor and hand piece (straight and contra – angle), fibre optic air rotor hand piece, Ultrasonic scaler & endo unit with different types of endo tips & Scaler tips – 10 each of endo tip and scaler, Oil Free Air Compressor (Medical Grade), have Air tank (capacity of 30-40 Lt.), have Auto cut-off switch, should supply Ergonomic Pneumatic stool. 2 Nos. (one for Dental surgeon and one for Assistant), One-year warranty, Having ISO, CE or USFDA certified. |  |
| 40. | <b>Dental X-ray Machine</b>  | Dental X-ray machine, very high frequency DC X-ray generator complete unit with complete accessories, Microprocessor based X-ray generator, Output rating: min. 65 KV selectable in steps of 1KV, compatible for RVG system, One-year warranty, Having ISO & CE or USFDA certified.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |
| 41. | <b>Dental Scaler</b>         | Dental Scaler, complete unit, Microprocessor/microcontroller-based system, piezoelectric technology, ten tips for scaler and one endodontic kit with ten sets of Ni Ti reamer and files, spreaders, pluggers, Autoclaveable hand piece, One-year warranty, Having ISO & CE or USFDA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np

अमरराज रेग्मा  
प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL



|     |                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |  |
|-----|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                         | certified.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |  |
| 42. | <b>Autoclave Dental</b>                 | Autoclave Dental with complete accessories, have digital timer for wet and dry cycle. cycles both for wrapped as well as unwrapped instruments, for flash sterilization, open, packed, liquids, Auto draining facility for reservoir tank water with separate tank for used and fresh water, Control panel to select cycle settings with LCD Display and water level indicator, Chamber volume approx. 20-25 liters, Mechanical Pressure release valve to release excess pressure, should supply Tray Stand: No. 1, Tray: Nos. 3, Bin (with lock): No. 1, One-year warranty, Having ISO & CE or USFDA certified.                                                                                                                                                                                                                                                                                                                                                                                                                                                            |  |
| 43. | <b>Color Doppler Ultrasound Machine</b> | A fully digital Color Doppler ultrasound DICOM compatible imaging system for Radiology, OB/Gyn, vascular, Cardiac, small parts applications, System shall have a at least 23"-inch-high resolution color monitor that has visual angle of left & right, and up & down visualization of images, and at least 13 inch touch screen control panel for ease of use during examinations, should have a minimum of 4 active probe/transducer connectors which can be all activated with electronic switching and fully inter-changeable, should support 3D/4D volume imaging, capable of capturing volumetric data quickly, should be capable of scanning up to 40 cm or more, should be able to support broadband convex, linear, transvaginal/ Endo cavity probe, phased array cardiac probes, micro convex probes and 4D probes, System should be able to support the following OB/GYN functions in future: Auto OB, Auto NT, Auto Follicle, Auto IMT, 4D package, should supply one pcs B/W Thermal USG Printer, One-year warranty, Having ISO, CE and USFDA(510k) certified. |  |
| 44. | <b>LED View Box (Single Film)</b>       | View box used for viewing the images of X-ray, CT/MRI at healthcare facilities, operates on mains electric supply, Ultra slim design, LED backlit and shall have separate on/off function with separate rotary continuous adjustable brightness control at the bottom of panel for convenient operation, Front sheet shall be made of polycarbonate or acrylic with antiglare, Illumination: High bright white LEDs, LED light source shall have at least 20000 hours of                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |  |



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भयागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |  |
|-----|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                               | operation, One-year warranty, having ISO, EU-CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| 45. | <b>Laryngoscope Set, Children &amp; Adult</b> | Laryngoscope set for children & adult, complete unit, shall have large hollow, cylindrical, slightly ribbed handle, Handle to be made of either chromium-plated or stainless steel, provision to insert two batteries, provision for fitting various sizes and types of depressors, shall come with a set of four stainless steel depressors, with halogen bulb of different sizes, shall be autoclaveable /sterilizeable, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                      |  |
| 46. | <b>Portable OT light</b>                      | Should have Memory Function, High quality sterilizable handle. With special European design for ventilation of heat. Body should be made of high-quality fire-resistant polymer, Intensity: 1,10,000 Lux $\pm 10\%$ , LED Life: >50000 Hrs., Number of LED: min. 75, Brightness Control: Capacitive Touch Panel, Diameter of Light : 500 mm, Focusing : Adjustable, Should have Battery Backup, one-year warranty, ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                        |  |
| 47. | <b>Ophthalmoscope, Direct</b>                 | Direct Ophthalmoscope, complete unit with all standard accessories, Compact system, operate on rechargeable battery, Light source: Halogen/Xenon bulb, dust free sealed optics, red free and cobalt blue filter, shall allow one-hand operation for streak focus and 360° streak rotation, universal convertible handle, shall have Nickel- Cadmium/Lithium ion rechargeable battery, Having ISO, CE (93/42 EEC Directives) or USFDA certified product                                                                                                                                                                                                                                                                                                                   |  |
| 48. | <b>Hospital Bed with mattress</b>             | Hospital Bed epoxy powder coated with high density PU foam mattress, shall be anti-corrosive and antirust treated epoxy powder coated welded steel bar or epoxy powder coated 16gauge perforated sheet top to improve ventilation, patient bed shall be fixed height with 2 sections where the backrest section could be elevated by mechanical hand crank located at the foot-end of the bed, Bedhead and foot-end panel (head and foot bows) shall be made of either between 4-6 anti-corrosive and antirust treated epoxy powder coated vertical tubular tube of not less than 30mm in diameter, Both bedhead and foot-end panel shall be detachable, Shall provide with one no. Two section mattress of dimensions at least (2000mm L x 900mm W) with washable cover |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np

वेबसाइट: jhimrukmun.gov.np  
अमरराज सेजवाल  
प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय  
OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |  |
|-----|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                                  | of good quality. The mattress must be made of high-density PU foam of 100mm thickness, having ISO ISO13485, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| 49. | <b>Trolley, Emergency (Emergency Crash Cart)</b> | Emergency trolley (Emergency Crash Cart) with removable colored bins, storage units, fitted with oxygen cylinder holder and four swivels castors, Frame work should be made of stainless steel tube, Should have two polystyrene boxes each with three drawers, Three shelves should be laminated/ stainless steel with railing, come with detachable plastic bins in six different color, overall size of: approx. 900 L x 450 W x 1500 H mm, mounted on 125 mm dia. Swivel castors, Having ISO, CE (93/42 EEC Directives) or USFDA certified product. |  |
| 50. | <b>Trolley, Dressing</b>                         | Basic trolley for transport of nursing supplies between departments in healthcare facilities, Stainless steel dressing trolley with 2 shelves, Heavy carriage mounted on 4 swivel anti-static castors, of which two with brakes, Fit on both sides with push bar-handle, Top and bottom shelves with guard rails, Overall: Approximately ( $\pm 10\%$ ) 900 x 550 x 1000mm (l x w x h), Frame, diameter: 30mm., Thickness of shelves: Approximately 1.5mm, one-year warranty, Having ISO, CE or USFDA approved product certificate.                     |  |
| 51. | <b>Trolley, Dressing</b>                         | Basic trolley for transport of nursing supplies between departments in healthcare facilities, Stainless steel dressing trolley with 2 shelves, Heavy carriage mounted on 4 swivel anti-static castors, of which two with brakes, Fit on both sides with push bar-handle, Top and bottom shelves with guard rails, Overall: Approximately ( $\pm 10\%$ ) 900 x 550 x 1000mm (l x w x h), Frame, diameter: 30mm., Thickness of shelves: Approximately 1.5mm, one-year warranty, Having ISO, CE or USFDA approved product certificate.                     |  |
| 52. | <b>Trolley, Medicine</b>                         | A medicine/drug trolley for storage and delivery of medicines and drugs to patients in wards of healthcare facilities, shall be constructed fully with 304 grade stainless steel sheet and tube or better, Overall size: approximately 900 H x 460 W x 760 L mm., Flat top of SS and at least 6 inch deep removable bucket at bottom, Multiple drawers (minimum 6) made of high quality materials with telescopic                                                                                                                                       |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”  
अमरराज सज्वाल

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |  |
|-----|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                                      | channels, below the platform, Minimum 6 small boxes to keep drugs, provision for hanging one IV fluid bottle, Shall be mobile on 4 x 50mm diameter (approx.) robust 360 deg., one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| 53. | Plaster Cutter                                       | Plaster Cutter with blades of different diameter, To cut all kinds of plaster bandages, have a fibre body, Blades must be corrosion resistant and highly durable and autoclaveable, Blades, have hexagonal mounting hole, supplied with 84mm, 74mm, and 64mm diameter blades, have a protective guard, Must be oscillating type, supplied with Carrying case to accommodate the plaster cutter and other accessories, one-year warranty, Having ISO 13485 and CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                  |  |
| 54. | Semi-Automatic CSSD Autoclave vertical 100 L or more | Semi-Automatic CSSD Autoclave vertical, capacity approx. 100 litres or more, complete with accessories, Single door high pressure steam sterilizer with triple wall, steam jacket and separate boiler, Shall have advanced microprocessor control system with LCD display, Sterilizer chamber SS 316, Door SS 316, Door Gasket: Silicon or better, Insulation: fibre glass resin bonded wool or better, Chamber capacity: approx. 100L or more, Autoclave shall work up to 121-134°C temperature, Pressure Range: 15-22 PSI, Spring loaded safety valves and automatic vacuum breaker for jacket, SS baffle for even steam distribution in the chamber, Safety lock for door: Pressure lock safety precautions for lid opening, one-year warranty, Having ISO, CE or USFDA approved product certificate. |  |
| 55. | Autoclave Electric (20 ltr or more)                  | Pressure cooker type portable steriliser unit for sterilising of surgical instruments and dressing materials by means of steam, Operating temperature 121 °C – 134 °C pressure 1.1 to 2.2 kg/cm <sup>2</sup> of steam pressure, Constructed of heavy-duty spun aluminium (preferably stainless steel), rectangular/cylindrical shape and must be seamless construction to prevent bacteria residue and dirt accumulation, one-year warranty, Having ISO 13485 and CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                              |  |
| 56. | Sphygmomanometer (BP apparatus) with stethoscope.    | Aneroid sphygmomanometer having a dial to show clear numbers and pointer / needle for measurement of pressure, Packed in easy carrying high quality pouch made of water-proof cloth to accommodate cuff, and inflation bulb, Must provide blood pressure cuffs for child size and for adult size (regular).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट : jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  |
|-----|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                              | Dual type stethoscope - Physician's stethoscope, Dual, cup/bell and diaphragm head, Head and ear tube assembly to be made of non-ferrous metal, Tubes to be synthetic material and ear tubes to have shaped plastic cushion ends, one year warranty, having ISO 9001 or ISO 13485 or better for medical devices.                                                                                                                                                                                                                                                                                                                                                                                                          |  |
| 57. | Handheld Pulse Oxymeter                      | Handheld Pulse Oxymeter, complete unit with all standard accessories, Display min. 3.5-inch TFT/LCD display or more, backlight illuminated, Parameters and waveform displayed- SpO2, pulse rate, system status, plethysmogram, menus for user settings, Spo2 dual-wavelength LED technique, Measuring mode should be continuous or spot check, Display SPO2 range: 0-100 %, Pulse rate measuring range must be 30-250bpm, Audio-visual alarms: High/low SpO2 and pulse rate, sensor off, sensor failure, low battery, have PC software for data communication, Inbuilt rechargeable battery and shall have battery back-up for at least 12 hours, one-year warranty, Having ISO, CE or USFDA approved product certificate |  |
| 58. | Pulse Oxymeter (Spot-Check)                  | It shall be suitable for professional clinical use, all patient categories neonate, infant and adult, LCD Colour Screen, Ultra compact pulse oxymeter integrated into finger/toe sensor clip, shall accommodates finger/toe thicknesses 8 to 25mm, Facility of spot-check of arterial blood oxygen saturation (SpO2) and Pulse Rate (PR), have one button operation, auto-off when not in use for 10 seconds, Easy readable display shows operational status, SpO2, PR, signal strength (bar graph) and battery status, one-year warranty, Having ISO 13485 and CE or USFDA approved product certificate.                                                                                                                 |  |
| 59. | Thermometer, Clinical, Digital               | Clinical digital thermometer to check the body temperature, Human oral use, Flat type, wide thermometer, safe to use, no glass, no mercury, Measurement range: 32°C to 45°C, shall work on a battery, Water proof for ease of cleaning, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                                                                                                                                                                                                                                                                                                                                                          |  |
| 60. | Weighing Machine with Height Measuring Scale | A pan type infant weighing scale for measurement of height and weight of neonates, digital baby scale with large clear digital display, Metric measurement in KG with a weighing range: 0-15kg, attachable length measure with measuring range from 35 to 80cm, Pan material: robust acrylic or moulded engineering ABS plastic, Fully enclosed construction makes for ease of cleaning, space saving and light weight to move, Shall come with rechargeable batteries and shall come with built-in charger or external battery charger.                                                                                                                                                                                  |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”  
अमरराज सेजुवाल

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |
|-----|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                                      | one year warranty, having ISO, CE or USFDA certified product.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |  |
| 61. | <b>Glucometer</b>                    | Portable handheld glucometer with Automatic lancing device for regular blood glucose self-monitoring purpose, LCD black/white display having Large numeric display (not less than 30 mm), Auto-shut off of meter when not in use, Data storage: at least 50 glucose measurements, each unit supplied with min. 50 Test strip, 50 lancets, Lancing device, and other accessories, having ISO, EU_CE/ USFDA(510) certified.                                                                                                                       |  |
| 62. | <b>Nebuliser, Baby</b>               | Heavy duty compact Nebuliser is required for paediatric use, Compact, lightweight, low noise, Durable long-life compressor. Suitable for heavy duty/ institutional (hospital) use, must be able to run uninterruptedly for one hour, Noise level must be less than or equal to 55 dBA, Piston-type electric aspirator that offers high performance and great durability, Nebuliser flow: 5 L/min, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                                      |  |
| 63. | <b>Bag Valve Mask (BVM)-Ambu Bag</b> | It shall be self-inflatable and must have pop up valve (non-return valve), attachment for oxygen tube & oxygen reservoir, Bag must be made up of medical grade silicon, latex free double layered which retain sensitivity and it must be resistant to rough use, Must be supplied with Oxygen reservoir bag of 2000ml and shall deliver tidal volumes of 500-800ml, shall be autoclavable, adaptable to all type of facemasks, come with appropriate sized facemasks, one-year warranty, Having ISO, CE or USFDA approved product certificate. |  |
| 64. | <b>IV Stand</b>                      | Adjustable IV/saline stand with five legs, with double hooks and five swivels castors, IV stand shall be made of tubular anti-corrosive and antirust treated epoxy powder coated mild steel, base fitted on mobile on swivelling castors of approx. diameter Ø50mm. The castors must be non-rusting and non-marking, height adjustable from approximately 1620mm to 2340mm, with a screw knob for height adjustment, one-year warranty, Having ISO, CE or USFDA approved product certificate.                                                   |  |
| 65. | <b>Fetal Doppler</b>                 | Fetal Doppler monitor shall be portable/handheld, lightweight and easy to carry, come with at least 2-inch colour LCD display with backlit to provide excellent display quality, should come with 2.5MHz Detachable ultrasound probe, Should come with In-built rechargeable Li-ion battery, Assure accurate FHR detection with clear sound, FHR measurement Range 50 – 199bpm, Working Mode: Continuous                                                                                                                                        |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित अर्थतन्त्र, सुवर्ण”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                 |  |
|-----|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                       | Wave Doppler, Should have Dual Audio Output for Providing enhanced quality fetal heart sound switch built-in loud speaker and headphone audio jack, One-year warranty, having ISO, EU-CE or USFDA approved product certificate.                                                                                                                                                                                                                 |  |
| 66. | Examination light     | Led cold light, Flexible arm, 5 wheel mobile stand, height/angle adjustable, 220V, 50Hz, Led life $\geq 50,000$ hours                                                                                                                                                                                                                                                                                                                           |  |
| 67. | BP apparatus adult    | A standard adult blood pressure (BP) apparatus (aneroid sphygmomanometer) features a measurement range of 0 to 300 mmHg with an accuracy of $\pm 3$ mm                                                                                                                                                                                                                                                                                          |  |
| 68. | Stethoscope           | overall length of about 27 to 28 inches (69 cm), a total weight of 120 to 180 grams, and a chestpiece made of surgical stainless st                                                                                                                                                                                                                                                                                                             |  |
| 69. | Pulse oximeter        | measures blood oxygen saturation (SpO <sub>2</sub> ) and pulse rate non-invasively using light absorption.                                                                                                                                                                                                                                                                                                                                      |  |
| 70. | Digital thermometer   | measures body temperature between 32.0°C and 43.0°C with an accuracy of $\pm 0.1^\circ\text{C}$                                                                                                                                                                                                                                                                                                                                                 |  |
| 71. | Adult weighing scale  | weight capacity of 150 kg to 300 kg with an accuracy or graduation of 100 g.                                                                                                                                                                                                                                                                                                                                                                    |  |
| 72. | Infant weighing scale | a specialized medical device designed with a curved, protected tray or sling to safely measure a baby's weigh                                                                                                                                                                                                                                                                                                                                   |  |
| 73. | Glucometer            | a compact medical device designed to measure blood glucose concentration quickly and accurately using a small drop of capillary, Typically ranges from 10 to 600 mg/dL, Most models store between 300 and 720 past test results with a date and time stamp.                                                                                                                                                                                     |  |
| 74. | Nebulizer             | Particle Size (MMAD): 1 to 5 micrometers ( $\mu\text{m}$ ) to reach the lower airways, Nebulization Rate: 0.2 to 0.4 milliliters per minute (ml/min), Medication Capacity: 6 to 10 milliliters (ml), Noise Level: Under 60 to 65 decibels (dB), Power Supply: AC adapter (220V/50Hz) or battery/USB-rechargeable for portable models. Unit Weight: 200 grams for compact/mesh types up to 1.3 to 1.9 kilograms for standard piston compressors. |  |
| 75. | Ambu bag adult        | a bag volume of about 1,500 ml to 1,600 ml, delivers a stroke tidal volume of roughly 700 ml to 1,300 ml, and is designed for patients weighing over 30 kg, Face Mask Size: Typically comes with a size 5 adult face mask, Oxygen Reservoir Bag Volume: Approximately 1,500 ml to 2,600 ml, Material: 100% latex-free medical                                                                                                                   |  |



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, पाथान  
BHYAGUTE, PATHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                               |                                                                                                                                                                                                                                                                                                                                                                                                                     |  |
|-----|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     |                               | grade silicone rubber (reusable)                                                                                                                                                                                                                                                                                                                                                                                    |  |
| 76. | Ambu bag pediatric            | handheld, self-inflating manual resuscitator designed to deliver temporary respiratory support to children. Below are its short specifications                                                                                                                                                                                                                                                                      |  |
| 77. | Ambu bag neonatal             | a handheld, medical-grade device designed to deliver emergency or supportive artificial ventilation to newborns and infants weighing under 10 kg                                                                                                                                                                                                                                                                    |  |
| 78. | Spine board                   | rigid patient-handling device used in emergency medical care to immobilize and transport people with suspected spinal or limb injuries                                                                                                                                                                                                                                                                              |  |
| 79. | IV stand                      | Stainless steel IV stand is a portable medical pole used to suspend intravenous fluid bags and medication bottles above a patient for continuous gravity or pump delivery, 4 bottle hooks arranged at the top, 4-leg star/rectangular weighted base for stability, Manual screw knob or twist-lock clutch collar                                                                                                    |  |
| 80. | Fetal doppler                 | fetal Doppler is a small, handheld ultrasound device used to detect and make a baby's heartbeat audible during prenatal care, Probe Frequency: 2.0 MHz to 3.0 MHz (standard continuous wave; 2 MHz for general/late stages, 3 MHz for early detection around 10–12 weeks), Heart Rate Range: 50 BPM to 240 BPM, Power Source: 2 AA batteries (3V DC) or a built-in rechargeable lithium battery with an AC adapter. |  |
| 81. | Delivery set                  | A normal delivery set is a collection of sterile, medical-grade stainless steel instruments used by healthcare providers during vaginal childbirth, episiotomies, and post-partum repair,                                                                                                                                                                                                                           |  |
| 82. | Catheterization set           | an all-in-one, sterile, single-use medical procedure pack designed for the safe, aseptic insertion of a urinary catheter                                                                                                                                                                                                                                                                                            |  |
| 83. | Laryngoscope with blade adult | a handheld medical device used to view the vocal cords and place a breathing tube into the trachea, grade stainless steel with a satin or brushed finish to reduce glare, Blade Sizes: Size 3 (medium/small adult, approx. 110 mm long) and Size 4 (large adult, approx. 130 mm long), LED or vacuum bulb, Battery-operated, Fully autoclavable and reusable                                                        |  |
| 84. | Laryngoscope with             | a medical device used to view the airway and insert breathing tubes in infants and children, grade stainless steel for corrosion                                                                                                                                                                                                                                                                                    |  |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित स्वास्थ्य र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np

वेबसाइट: jhimrukmun.gov.np

अमरराज सेजुवाल  
प्रमुख प्रशासकीय अधिकृत



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते प्युठान  
BHYAGUTE PYUTHAN



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|     |                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |  |
|-----|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
|     | blade pediatric          | resistance and durability.; Used for older children, placed in the vallecula to indirectly lift the epiglottis,LED or vacuum bulb, Battery-operated, Fully autoclavable and reusable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |
| 85. | Dressing drum            | A dressing drum is a cylindrical stainless steel container used to sterilize, store, and transport medical dressings, gauze, and surgical instruments.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |  |
| 86. | Kidney tray              | kidney tray (also called an emesis basin or kidney dish) is a shallow, curved medical container shaped like a human kidney                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |
| 87. | Bedpan                   | Reusable shallow, rigid receptacle used for the collection of feces and urine from bedridden or limited-mobility patients,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |  |
| 88. | Urine measurement jug    | a graduated medical container used to accurately measure a patient's liquid waste output,Usually holds between 800 ml and 1000 ml, Made from durable clear plastic like polypropylene                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |  |
| 89. | Commode chair            | portable, toilet-like chair designed for individuals with limited mobility, such as the elderly or postoperative patients,Made from heavy-duty steel,Standard models support 250 to 300 lbs                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |
| 90. | Patient transfer trolley | a mobile medical stretcher used to safely move patients between hospital rooms, departments, or treatment areas,Weight Capacity: 150 kg to 250 kg safe working load,Dimensions (Approximate): 2000–2100 mm (Length) x 550–700 mm (Width) x 650–850 mm (Height),Frame Material: Mild steel or stainless steel tubular pipes with an epoxy powder-coated finish for rust resistance,Mobility: Four swivel castors (usually 125 mm to 200 mm diameter), with at least two equipped with locking brakes.Backrest: Manual or ratchet-adjustable elevation (0 to 65–80 degrees).Mattress Platform: Waterproof polyurethane (PU) or foam mattress with a vinyl/leatherette cover |  |
| 91. | Bed mattress             | an engineered sleep surface designed to support the body, align the spine, and relieve pressure points during rest,Twin / Single: 38 inches × 75 inches (99 cm × 190 cm),Soft (Scale 3–5): Best for lighter-weight sleepers and side sleepers to cushion shoulders and hips.Medium to Medium-Firm (Scale 5–7): Ideal for back sleepers and average-weight users to maintain spinal alignment.Firm (Scale 7+): Recommended for stomach sleepers and heavier individuals to prevent deep sinkage                                                                                                                                                                            |  |



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|      |                     |                                                                                                                                                                                                                                                                                                                  |
|------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 92.  | Pillow              | Standard bed pillows measure 20 x 26 inches (51 x 66 cm) size, Common options include memory foam, down, latex, and microfibre.                                                                                                                                                                                  |
| 93.  | Bed Sheet           | A green bed sheet typically features 100% cotton or microfiber fabric, standard single-to-king sizing, and breathable, size fade-resistant properties, Queen / Double: ~90 x 90 inches or fitted options with elastic corners.                                                                                   |
| 94.  | Peri Light          | Medical LED Examination Lights, Light Source High-efficiency integrated LED (typically 7 x 1W or a single 5.5W power-saving bulb), Operating Voltage 210V – 240V AC, 50/60 Hz, Mild Steel (MS) powder-coated dome with a chrome-plated or heavy-duty plastic mobile base, 60 cm to 70 cm flexible gooseneck arm. |
| 95.  | Stool               | Patient Stool Revolving A with stainless steel frame, adjustable height and footrest ring designed for hospitals, Four Leg Base, Height Range 460 - 660 mm                                                                                                                                                       |
| 96.  | Vaginal Speculum    | a crucial diagnostic medical device used by healthcare providers to dilate the vaginal walls, Reusable Metal: Made from high-quality, corrosion-resistant austenitic stainless steel, Most common standard; used for adult routine exams.                                                                        |
| 97.  | Otoscope            | A standard otoscope is a hand-held medical device used to examine the ear canal and eardrum, typically featuring 3x lens magnification and a 2.5V light source, Material: Durable surgical-grade stainless steel, chrome-plated brass, or high-impact thermoplastic housing.                                     |
| 98.  | Nasal Speculum      | A nasal speculum is a handheld medical tool designed to dilate the anterior nares for examination and minor nasal procedures, Material: Premium surgical-grade stainless steel,                                                                                                                                  |
| 99.  | Nasal Prong         | A nasal prong is a lightweight, single-use medical device designed to deliver low-flow supplemental oxygen directly into the nostrils, Material: Medical-grade, soft polyvinyl chloride.                                                                                                                         |
| 100. | Non Rebreather Mask | A Non-rebreather mask is an emergency medical device used to deliver high-concentration supplemental oxygen to spontaneously breathing patients.                                                                                                                                                                 |

सुमनराज सेजुवाल  
प्रमुख कार्यकारी अधिकृत

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY



गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भ्यागुते, प्युठान  
BHYAGUTE, PYUTHAN

लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|      |                                   |                                                                                                                                                                                                                                                                                                                                                                                        |
|------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 101. | <b>Nebulisation mask</b>          | A standard nebulization mask is a clear, medical-grade plastic device used to deliver liquid medication directly into a patient's respiratory system as an aerosol mist, Material: Non-toxic, medical-grade polyvinyl chloride.                                                                                                                                                        |
| 104. | <b>Nasogastric Tube (NG tube)</b> | nasogastric (NG) tube is a thin, flexible plastic catheter passed through the nose and down into the stomach for feeding, medication administration, or gastric decompression/suction, Length: Typically 90 to 125 cm for adults,                                                                                                                                                      |
| 105. | <b>Foley Catheter</b>             | adult Foley catheter is a flexible sterile tube featuring an outer diameter of 14 to 16 French (Fr) (approx. 4.7 to 5.3 mm) and a retention balloon capacity of 10 mL, Length: Standard adult length is approximately 15 to 18 inches (approx. 40 cm).                                                                                                                                 |
| 106. | <b>Stappler Remover</b>           | 3M Precise disposable skin staple removers have been designed to provide a fast and easy method of removing all brands of surgical skin staples, Manufactured in premium grade stainless steel.                                                                                                                                                                                        |
| 107. | <b>Foot Step</b>                  | Frame made of Round Tube. The body section is mounted on Rubber Shoes. Foot Step is Double Step. The top is made of Metal. Product Size : 45 L x 45 W x 45 H cms, Material Metal.                                                                                                                                                                                                      |
| 108. | <b>Jobson Horne Probe</b>         | Single use probe designed for wax removal and cotton application. Length = 150mm. Loop Diameter = 3.0mm. Material = Carbon filled Nylon, Manufactured in premium grade stainless steel.                                                                                                                                                                                                |
| 109. | <b>Crocodile Forcep</b>           | a spring-loaded, finger-ring handle and a slender shaft designed with a single-action top jaw that opens like an alligator's snout, Overall Length: Typically ranges from 8 cm to 14 cm (3.5 to 5.5 inches) for standard ear and nasal procedures, Material: Premium-grade, autoclavable surgical stainless steel (commonly 410 or 420 grade) for corrosion resistance and durability. |
| 110. | <b>Tilley's Forcep</b>            | Standard Tilley's forceps are angled, non-toothed surgical instruments primarily used in Ear, Nose, and Throat (ENT) procedures for placing or removing nasal and aural dressings, packing, or foreign objects, Material: Forged from medical-grade, corrosion-resistant stainless steel (such as martensitic).                                                                        |
| 111. | <b>Wax Hook</b>                   | typically 14 cm to 15 cm long, made of surgical-grade stainless steel, and features a fine, blunt curved tip designed to safely extract hardened earwax or foreign objects.                                                                                                                                                                                                            |

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुदृढ आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np



झिमरुक गाउँपालिका  
JHIMRUK RURAL MUNICIPALITY

गाउँ कार्यपालिकाको कार्यालय

OFFICE OF THE RURAL MUNICIPAL EXECUTIVE

भयागुते, लुम्बिनी  
BHYAGUTE, LUMBINI



लुम्बिनी प्रदेश, नेपाल  
LUMBINI PROVINCE, NEPAL

|  |  |             |  |
|--|--|-------------|--|
|  |  | TOTAL       |  |
|  |  | VAT         |  |
|  |  | GRAND TOTAL |  |

Note : kindly mentioned if any deviation

email : info@jhimrukmun.gov.np

: jhimrukmun@gmail.com

2073/08/02  
अमरराज सेजुवाल  
प्रमुख प्रशासकीय अधिकारी

“झिमरुक गाउँपालिकाको समृद्धिको आधार: व्यवसायिक कृषि, पर्यटन तथा वाणिज्य, सुरक्षित आवास र पूर्वाधार”

इमेल : jhimrukmun@gmail.com , info@jhimrukmun.gov.np वेबसाइट: jhimrukmun.gov.np